

SPRx32

Keep your PIN code safe Universal Connectivity



Technical data

Host interface	<ul style="list-style-type: none"> • CCID compliant • SPR132: Full speed USB (12 Mbps), bus powered • SPR332: PnP RS232 (115,200 bps) • SPR532: Dual Mode (USB and RS232)
Smart Card Interface	<ul style="list-style-type: none"> • T=0, T=1 protocol support • Memory card support • Communication speed up to 115,200 bps (PPS, FI parameter) • Frequency up to 12 MHz (PPS, DI parameter) • Support ISO 7816 Class A and AB card
Smart Card Connector	<ul style="list-style-type: none"> • 8 contacts - ISO location • Certified for 100,000 insertions • Sliding contact (landing optional)
Human Interface	<ul style="list-style-type: none"> • 2 LEDs and buzzer indicating status • 3 x 4+1 keypad • Tamper evident
Cable/Power	<ul style="list-style-type: none"> • 1.5m long with USB type A connector Or in Dual Mode also • 1.5m long with F-DB9 and Pass-through PS/2
Dimension	<ul style="list-style-type: none"> • LWH 120x70x40 mm
Operating Temp.	<ul style="list-style-type: none"> • 0° to 50° Celsius
OS	<ul style="list-style-type: none"> • Windows® 98, ME, NT4, 2000 and XP • Windows® CE, MacOS X (Q3'03) • Linux, Solaris (Q2'03)
API	<ul style="list-style-type: none"> • PC/SC • CT-API (thru wrapper on top of PC/SC)
Approval	<ul style="list-style-type: none"> • FCC Class B part 15, cULus, CE, VCCI • Microsoft® WHQL 98, ME, 2000, XP • USB • EMV Level I • Common Criteria EAL 3+ High • HBCI compliant

Overview

The SPRx32 is based on SCM Microsystems' STC II micro controller. This device supports multiple interfaces, multiple reader devices and relevant security standards. Together, these features provide SCM Microsystems with the unique ability to offer an efficient, high performance, cost effective solution that combines USB and Serial connections via a removable cable (SPR532).

The SPRx32 is specifically designed to protect your PIN code from theft or unauthorized sources while connected to the network. It provides the next level of security by allowing your PIN code to be entered locally and safely on the reader itself without being transmitted to your untrusted PC.

The SPRx32 is ideal for secure web access, online banking and sensitive database access such as personnel or healthcare records. On-board flash enables future firmware and application enhancements that guarantee against obsolescence.

SPRx32 Benefits

- Secure PIN entry to Smart Card
- On-board flash provides seamless secure firmware upgrades in the field
- EMV Level I AND PC/SC certification based on a single solution
- Common Criteria (CC EAL 3+ High) certified
- USB (SPR332) or Dual host interface (USB and RS232, SPR532)
- High performance
- Fully tested and compliant with all major Smart Cards in the market
- Customizing options: casing, colors, and company logo

The SCM Microsystems Advantage

SCM Microsystems brings over a decade of experience in ASIC and Smart Card Reader development to this unique product, including:

- More than 60 patents
- Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and Smart Card industry leaders
- Industry endorsed SmartOS™ middleware
- Direct significant long-term relationships with all leading Smart Card manufacturers and application providers
- High quality mass production capability

US Headquarters
SCM Microsystems Inc.
466 Kato Terr.
Fremont, CA 94539, USA
email: adapter@scmmicro.com
Phone +1 510 360 2300
Fax +1 510 360 0211

European Headquarters
SCM Microsystems GmbH
Oskar-Messter-Str. 13
D-85737 Ismaning, Germany
email: sales@scmmicro.de
Phone +49 89 9595 5000
Fax +49 89 9595 5555

SCM Microsystems, Japan Inc.
8F Hirakawacho Ronstate,
2-11-1, Hirakawacho-cho,
Chiyoda-ku, Tokyo, Japan
Postal code: 102-0093
email: sales@scmmicro.co.jp
Phone +81 3 3511 8511
Fax +81 3 3511 8516

SCM Microsystems France
ZE Athélie II - n° 216,
Avenue du Serpolet
13704, La Ciotat, Cedex, France
email: sales@scmmicro.fr
Phone +33 442 838 000
Fax +33 442 838 001

SCM Microsystems Asia Pte. Ltd.
25 Serangoon North Ave 5
#06-00 Keppel Digihub
Singapore 554914
email: sales@scmmicro.com.sg
Phone +65 6551 5233
Fax +65 6483 0210

SCM Microsystems, Netherlands
De Tweeling 20A
5215 MC's-Hertogenbosch
The Netherlands
Phone +31 73 690 2690
Fax +31 73 690 2695

Secure Micro Technologies, India Pvt. Ltd.
Module No. 0308
3rd Floor, D Block-South
Tidel Park
4, Canal Bank Road
Taramani, Chennai 600 113, India
email: sales@scmmicro.co.in
Phone +91 44 2254 0636
Fax +91 44 2254 0645

